# Photoinduced Segregation Behavior in 2D Mixed Halide Perovskite – effects of light and heat

Tik Lun Leung,<sup>1,3,‡</sup> Zhilin Ren,<sup>1,‡</sup> Ali Asgher Syed,<sup>1</sup> Luca Grisanti,<sup>2</sup> Aleksandra B. Djurišić<sup>1\*</sup> and Jasminka Popović<sup>2\*</sup>

<sup>1</sup>Department of Physics, The University of Hong Kong, Pokfulam Road, Hong Kong; email: <u>dalek@hku.hk</u>

<sup>2</sup> Ruđer Bošković Institute, Bijenička 54, Zagreb, Croatia; email: <u>Jasminka.Popovic@irb.hr</u>

<sup>3</sup> School of Physics, The University of Sydney, Sydney, NSW, 2006 Australia

## Abstract

Photoinduced halide segregation (PHS) is a process of critical importance for the performance of perovskite solar cells with mixed halide absorber layers. However, PHS is still not well understood, especially in the case of layered metal halide perovskites (MHP), which are less commonly studied compared to their 3D counterparts. Here we investigated temperature- and light-induced PHS in 2D MHP with phenylpropylammonium (PPA) spacer. We found that 2D PPA-based MHP exhibited complex segregation behavior dependence on temperature and illumination intensity, with suppression of segregation observed at high temperature (attributed to highly exothermic nature of the process), as well as moderate illumination intensities, illustrating importance of additional processes present in this particular material, which exhibits distinctly different behavior compared to 2D MHPs with other aromatic cations.

Metal halide perovskites have widely tunable bandgaps by simple composition adjustments. They have a general formula of ABX<sub>3</sub>, where A= MA, FA or Cs, B= Sn or Pb, and X= I, Br or Cl. With different combinations of A, B and X ions, the bandgap can be varied from 1.24 eV to 3.55 eV.<sup>1</sup> Wide range of bandgap tunability, coupled with versatile preparation procedures, enables new solutions to existing challenges such as deep blue light emitting diodes (LEDs)<sup>2,3</sup> and multi-junction photovoltaics (PVs).<sup>4-6</sup> While the multi-junction perovskite-Si tandem cells have recently reached a power conversion efficiency (PCE) of 29.5%,<sup>7</sup> exceeding the theoretical limit of single silicon cell,<sup>8</sup> challenges remain in terms of device stability. The ideal bandgap of the top absorber in a tandem cell is about 1.7 eV which can be easily achieved by halide mixing method. However, mixed halide perovskites (MHPs), noted as AB(I<sub>1-x</sub>Br<sub>x</sub>)<sub>3</sub>, are commonly observed to segregate under illumination, i.e. exhibit photoinduced halide segregation (PHS) to form iodide-rich domain with lower bandgap energy behaves as a carrier sink which can cause opencircuit voltage (V<sub>oc</sub>) deficit.<sup>11</sup> Although the correlation between vacancy and PHS has been evidenced,<sup>12,13</sup> mechanisms of PHS are still not well understood.

Different models have been proposed to describe PHS. The two commonly used models are thermodynamic miscibility gap model<sup>14,15</sup> and polaron model.<sup>16,17</sup> According to miscibility gap model,<sup>14,15</sup> PHS is a thermodynamic governed process where the illumination can provide energy to overcome the energy barrier of separating the mixed phase, and halide segregation does not occur when the illumination drops below threshold intensity which is determined by material properties and the temperature. In a polaron model,<sup>16,17</sup> segregation is a carrier-driven process where the energy difference of the parent mixed phase and lower bandgap phases lead to carrier funneling which, coupled with the lattice structure, induces polaron formation. Neither of the two common models is fully able to explain the contradictory experimental observations simultaneously, namely remixing of the segregated phases at high temperature,<sup>18,19</sup> and the insensitivity of terminal composition to temperature.<sup>20</sup> Another thermodynamic model, thermodynamic energy bandgap model,<sup>20</sup> which attempted to reconcile the predictions of the two models, predicted a terminal composition close to zero, and the difference with experimental observations was attributed to kinetic limitations and a temperature-independent percolation threshold.<sup>20</sup> In addition to differences in the prediction of terminal composition and its temperature dependence, the predicted illumination values for illumination suppression also vary greatly, with low illumination levels (~20 to 230  $\mu$ W cm<sup>-2</sup>) estimated by miscibility gap and high illumination levels (0.75 to 200 W cm<sup>-2</sup>) estimated by polaron model. In addition, the importance of hole trapping and oxidation of iodide species has been recently recognized.<sup>21,22</sup> Obviously, further refinement of PHS models is necessary due to its complex nature that includes several factors which cannot be distinguished easily.

In addition, while PHS in 3D perovskites is widely investigated, limited knowledge exists for PHS and ion migration in layered Ruddlesden-Popper (RP) and/or Dion-Jacobson (DJ) perovskites.<sup>23-30</sup> which have a general formula  $L_2A_{n-1}B_nX_{3n+1}$  (RP) or  $LA_{n-1}B_nX_{3n+1}$  (DJ), where L is the bulky organic spacer cation and n is the number of octahedral lead halide layers sandwiched between spacer cation bilayers. Similar to 3D perovskites, the divergence between different PHS models persists in these materials as well, and its interpretation is further aggravated by the effect that the choice of spacer cation has on PHS, which is absent in 3D perovskites. Despite increased complexity, elucidation of processes occurring in 2D MPH are particularly important since those materials demonstrated significant ability to suppress the halide segregation. Several spacer cations were found to impede halide segregation, for example butylammonium (BA) spacer for electric field driven halide segregation in LEDs<sup>23</sup> and benzylammonium (BZA) spacer for PHS under 200 mW cm<sup>-2</sup> LED light soaking at 85 °C.<sup>24</sup> Furthermore, a rigid spacer of phenethylammonium (PEA) was found to significantly suppress PHS in 2D MHP, compared with the BA spacer.<sup>25</sup> Thus, it is critical to improve our understanding of the PHS to fully utilize the use of 2D MHP to develop PHSresistant devices. Unfortunately, the problems with different models developed for PHS in 3D perovskites also extend to their 2D counterparts. For example, the activation energy of PHS in  $PEA_2Pb(Br_{0.5}I_{0.5})_4$  was 21.7 kJ mol<sup>-1</sup> which is smaller than that in MAPb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>3</sub> (28.9 kJ mol<sup>-1</sup>),<sup>18,26</sup> which would indicate that PHS in PEA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> would be more pronounced compared to MAPb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>3</sub>, different from experimental observations. Recently, study on mixing-demixing process in (PDMA)Pb(Br0.5I0.5)4 (PDMA: 1.4-phenylenedimethanammonium) thin film revealed a miscibility gap under illumination which supports the idea that the process is governed by thermodynamics rather than kinetics.<sup>27</sup> This implies that the segregation resistance cannot be evaluated by comparing the activation energies in different MHPs due to different experiment conditions, such as sample preparation methods (which would affect the grain sizes and defect levels in the samples and consequently ion migration) and illumination intensities. It has been well recognized that there are still several unanswered questions concerning PHS, and that the analysis is complicated by conflicting data in the literature.<sup>31,32</sup> To rationalize the diverging phenomena, we investigate the PHS dependence on temperature and illumination intensity in a 2D MHP. We have developed an *in-situ* absorption measurement to monitor the halide composition of 2D MHP with phenylpropylammonium (PPA) spacer under illumination. Since it has been shown that layered perovskites with aromatic and aliphatic spacer cations show distinctly different behavior<sup>25</sup> and that PHS and/or ion migration are strongly dependent on the spacer cation used,<sup>25,29,30</sup> we have chosen PPA cation as an aromatic spacer with a longer alkyl chain tail compared to more commonly studied PEA. As shown in Figures S1 and S2, PPA-based perovskite exhibits significantly different behavior compared to both BZA and PEA, where for PEA we observe suppressed segregation at both 25°C and 84°C, for BZA we observe no suppression at both temperatures, while for PPA we observe suppression only at 84°C (for a given illumination intensity of 6.5 mW/cm<sup>2</sup>). This makes PPA an excellent candidate for performing comprehensive investigation of PHS as a function of both temperature and light intensity, as it has potential to uncover complex behavior that can eventually lead to better understanding of this important phenomenon. In addition, the investigation of PHS over a wide range of temperature and illumination intensities is important as the solar cells operating outdoors will be exposed to wide range of conditions, and those operating indoors (perovskite solar cells are particularly promising for indoor applications<sup>33,34</sup>) are operating at significantly lower illumination intensities compared to 1 Sun (100 mW/cm<sup>2</sup>).


A complex dependence of the segregation on temperature and illumination intensity was indeed observed for this material for the investigated illumination power (6.5-100 mW/cm<sup>2</sup>) and temperature (25-84°C). The segregation process was then interpreted in the aspects of kinetics and thermodynamics with Arrhenius and Van't Hoff equations, respectively. At the lowest illumination intensity (6.5 mW/cm<sup>2</sup>), the photoinduced segregation can be well described by Van't Hoff equation. With the increase of illumination intensity, other mechanisms start to dominate the process and a more complex behavior emerges which can no longer be approximated by a simple linear function. At rarely considered moderate illumination intensities around 0.1 Sun, particularly interesting behavior of segregation suppression at both high temperature and increased illumination intensity was found, which was attributed to the thermodynamic nature of PHS, instead of its kinetic property. Further increase of the illumination intensity, however, leads to re-emergence of segregation, which can be attributed to increased effects of hole trapping and/or polaron-induced strain. Interestingly, the segregation at high intensity can be described by bi-exponential process at lower temperatures but it can be described with a single exponential function again at 84°C.

The 2D perovskite film of PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> was deposited on glass substrate by spin-coating in an argon filled glovebox. Pure bromide and pure iodide 2D perovskite thin films were also prepared as for reference. A homogenously mixed halide perovskite was obtained, as evidenced by the exciton peak at 450 nm in the absorption spectrum (Figure S3), which is in agreement with other 2D mixed halide perovskites (MHPs).<sup>25,26</sup> The XRD patterns of PPA<sub>2</sub>PbI<sub>4</sub> PPA<sub>2</sub>PbBr<sub>4</sub> and PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> are shown in Figure S4. Although bromide is smaller than iodide, PPA<sub>2</sub>PbBr<sub>4</sub> structure exhibit larger periodicity along the cdirection (d = 19.35 Å) compared to PPA<sub>2</sub>PbI<sub>4</sub> which exhibits periodicity of d = 16.9 Å. This indicates that the packing of the spacer cations and the intermolecular interactions within the bilayer have stronger influence on the contraction/expansion of the unit cell than the difference in sizes of the halide ions. This is often not the case with alkylammonium spacer, such as butylammonium. But various types of  $\pi$ - $\pi$ interactions, that can be established when alkylphenylammonium spacers are used, seems to have the prevailing effect on the overall size of unit-cell. The same as in the case of PPA, the smaller unit was reported for the iodide structure with phenylethylammonium (PEA) compared to its bromide analogue. 35,36 So, while the pure bromide shows larger interlayer distance than the pure iodide PPA-based perovskite, the interlayer distance of PPA MHP (d = 19.51 Å) exceeds those of both pure halide perovskites. Since the difference between PPA<sub>2</sub>PbI<sub>4</sub>, PPA<sub>2</sub>PbBr<sub>4</sub> and PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> is not caused only by the (partial) substitution of halides on crystallographic B site but instead it also includes the reorganization of spacer bilayer accompanied with the conformational changes of PPA cations, Vegard's law is not applicable, thus making XRD unsuitable method to investigate PHS. In order to continuously follow the PHS and prevent remixing process in dark, the *in-situ* visible absorption measurements with a xenon lamp as excitation source and AM0 filter were conducted (Figure S5). Films were encapsulated with cover glass and epoxy to prevent potential degradation due to oxygen and moisture.<sup>37</sup> The absorption spectra were obtained from the light transmittance with Beer-Lambert law. The obtained *in-situ* absorption exhibits a minor blue shift in exciton peak when compared with the steady-state absorption spectrum [Figure S6].

Figure 1a shows the *in-situ* absorption spectra of  $PPA_2Pb(Br_{0.5}I_{0.5})_4$  film at 25 °C for 30 min. Under prolonged illumination, the intensity of exciton peak at 443.0 nm decreases and blue-shifts with a simultaneous increase of absorption intensity at longer wavelengths. Blue shifting of the parent peak indicates bromide enrichment in the parent phase while the emerging absorption implies the formation of iodide-rich phase. The segregation process can be described by Eq. 1

$$2PPA_2Pb(Br_{0.5}I_{0.5})_4 \xrightarrow{h\nu} PPA_2PbBr_4 + PPA_2PbI_4$$
(1)

This observation resembles the PHS in 2D MHPs with other spacer cations.<sup>25,26</sup> Also, the newly evolved exciton peak at longer wavelength agrees with the formation of iodide rich phase during halide segregation.<sup>15,38</sup> The increased peak width suggests that the segregated sample is composed of a wide range of halide compositions. To visualize the composition changes, the absorption difference spectrum was obtained by subtracting the initial spectrum (Figure 1B). The absorption difference spectrum clearly exhibits a depletion of the parent composition, accompanied with the growth of bromide-rich and iodide-rich phases. The equilibrium state between the mixed and segregated phases can be revealed by two isosbestic points at 422 nm for the mixed-bromide rich phases and 456 nm for the mixed-iodide rich phases. The composition change was quantified by integrating the peak area in absorption difference spectrum and plotted as a segregation trace (Figure 1C). The trace was fit with monoexponential function; pseudo-first-order rate constant (*k*) of  $3.04 \times 10^{-4} \text{ s}^{-1}$  was obtained. The obtained rate constant is comparable to the value obtained with PEA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> film ( $4 \times 10^{-4} \text{ s}^{-1}$  at 100 mW cm<sup>-2</sup> and 295K)<sup>26</sup> and it is an order magnitude smaller than that with (PDMA)Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> film ( $6 \times 10^{-2} \text{ s}^{-1} \text{ at } 1.5 \text{ mW cm}^{-2} \text{ and } 313 \text{ K}$ ),<sup>27</sup> but neither of them showed obvious segregation in the given condition. Thus, it should be noted that the degree of segregation cannot be revealed by the rate of reaction.




**Figure 1.** (a) *In-situ* absorption spectra recorded at different times during the segregation process of  $PPA_2Pb(Br_{0.5}I_{0.5})_4$  at 25 °C under a xenon lamp with 6.5 mW cm<sup>-2</sup> (b) absorption difference spectra and (c) segregation trace.

The photoinduced halide segregation process in the PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> films was further investigated at elevated temperatures. The *in-situ* absorption spectra, absorption difference spectra and corresponding segregation traces recorded at different times during the segregation process of PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> at T = 41 °C, 56 °C, 71 °C and 84 °C under a xenon lamp with 6.5 mW cm<sup>-2</sup>, are shown in Figure S7. With an increase in temperature, the rate constant increases from  $3.04 \times 10^{-4}$  s<sup>-1</sup> at T = 25 °C to  $3.36 \times 10^{-3}$  s<sup>-1</sup> at T = 84 °C. The influence of temperature on the rate constant can be expressed with the Arrhenius equation (Eq. 2).<sup>18</sup>

$$\ln(k) = -\frac{E_a}{RT} + \ln(A)$$
<sup>(2)</sup>

where A is a pre-exponential factor,  $E_a$  is the activation energy of photoinduced halide segregation process, R is the universal gas constant and T is temperature, as shown in Figure 3b. Although the rate of segregation reaction increases with temperature, as can also be seen from the Arrhenius diagram where ln(k) decreases linearly with 1/T, one should always keep in mind that the reaction rate itself does not address the extent of segregation reaction, as this is actually controlled by thermodynamic factors (*vide infra*). This is seen at highest temperatures where the reaction rates are largest while the segregation is almost suppressed. Figure 2a shows almost no bromide enrichment of parent phase nor the formation of iodide-rich phase at the temperatures of 71 ° C and 84 ° C. The extent of the segregation reaction and corresponding thermodynamic equilibrium will be addressed and discussed later. From Figure 2a it can also be seen that segregation readily occurs even at room temperature despite the activation energy, calculated from the slope of the Arrhenius diagram, of  $32.0 \pm 3.8$  kJ mol<sup>-1</sup>. The obtained value is larger than that of PEA<sub>2</sub>Pb(Br<sub>0.5</sub>J<sub>0.5</sub>)<sub>4</sub> (21.7 kJ mol<sup>-1</sup>) which has shown negligible halide segregation under 1 sun.<sup>26</sup>

In addition to temperature, excitation intensity has been shown to have an important effect on the photoinduced halide segregation processes. Threshold excitation intensity was introduced to explain the absence of segregation at low intensity (in a range from ~20 to 230  $\mu$ W cm<sup>-2</sup>).<sup>17,18</sup> On the other hand, it was reported that the segregated phases remixed at high intensity (0.75 to 200 W cm<sup>-2</sup>).<sup>39,40</sup> To elucidate the effect of excitation intensity on the photoinduced segregation processes in the PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> films, we further investigated the segregation processes at moderate light intensities in between the low and high intensity extremes commonly investigated in the literature, i.e. with illumination intensity significantly affects the segregation process at *T* = 25 °C, while the impact of intensity on the segregation occurring at *T* = 84 °C is insignificant.



**Figure 2.** *In-situ* absorption spectra of PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> recorded at t = 0 s and exposed to a xenon lamp for 30 min under different conditions. (a) T = 25 °C, 41 °C, 56 °C, 71 °C and 84 °C at 6.5 mW cm<sup>-2</sup>, (b) T = 25 °C and (c) T = 84 °C at 6.5 mW cm<sup>-2</sup>, 9.5 mW cm<sup>-2</sup> and 12.0 mW cm<sup>-2</sup>.

The *in-situ* absorption spectra, absorption difference spectra and segregation traces recorded at different times during the segregation process of PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> at T = 41 °C, 56 °C, 71 °C and 84 °C under a illumination of 9.5 mW cm<sup>-2</sup> and 12.0 mW cm<sup>-2</sup> are shown in Figure S8 and S9, respectively. The obtained rate constants were presented in Figure 3a and Table S1. At low temperature, the increase of intensity accelerates the segregation process significantly. This is expected since the higher excitation power assists in overcoming the activation barrier.<sup>7</sup> However, with the increase in temperature, at T = 56 °C and 71 °C, the impact of increased intensity on the rate of segregation gradually diminishes. Finally, at T =84 °C, photoinduced segregation processes under all three illuminating conditions have almost the same rate. Furthermore, it is important to notice that under the illumination of 6.5 mWcm<sup>-2</sup>, the rate of reaction in whole temperature range strongly depends on the temperature. However, for 9.5 mW cm<sup>-2</sup> and 12.0 mW  $cm^{-2}$  the segregation rates do not depend on temperature in the range from 25 °C to ~70 °C. In short, the kinetics of segregation reactions under 6.5 mWcm<sup>-2</sup> is temperature-driven while in the case of increased intensity the kinetics of segregation is primarily determined by the intensity. Although the rate constant at 12 mW cm<sup>-2</sup> is comparable to that in 84 °C at 6.5 mW cm<sup>-2</sup> ( $3.36 \times 10^{-3}$  s<sup>-1</sup>), PHS is readily observed in the former while it is absent in the later. This result clearly differentiates kinetic and thermodynamic properties of PHS in our sample.

Figure 3b-d shows Arrhenius diagrams for the segregation reactions under 6.5 mW cm<sup>-2</sup>, 9.5 mW cm<sup>-2</sup> and 12.0 mW cm<sup>-2</sup>. We can observe that at higher excitation (9.5 mW cm<sup>-2</sup> and 12 mW cm<sup>-2</sup>), the observed dependence can no longer be described with a single linear function. This indicates that additional mechanisms start to dominate the reaction, and consequently we can distinguish two different regions at high temperature (temperature dominated region, TDR) and low temperature (light dominated region, LDR). The data in each region were fitted by a straight line, and for TDR one additional temperature data point has been added. The activation energy for the segregation under 6.5 mWcm<sup>-2</sup> is  $32.0 \pm 3.8$  kJ mol<sup>-1</sup>. For both 9.5 mW cm<sup>-2</sup> and 12 mW cm<sup>-2</sup>, activation energies in TDR are of the same order of magnitude as at lower power (91±29 kJ mol<sup>-1</sup> and 42.1±1.5 kJ mol<sup>-1</sup>, respectively), while in LDR the activation energy is reduced by an order of magnitude, i.e. low values of  $3.5 \pm 0.8$  kJ mol<sup>-1</sup> and  $3.6 \pm 2.2$  kJ mol<sup>-1</sup> are obtained. This suggests that the shift from the temperature-dependent regime to the intensity regime remarkably reduces the activation energy. In the intensity regime, increase of the intensity mainly results in the increase of the reaction rate with only a slight change of activation energy.

Finally, we address the thermodynamic aspects of photoinduced segregation processes in the  $PPA_2Pb(Br_{0.5}I_{0.5})_4$  films. If the photoinduced segregation process described by the Eq. 1 is assumed to be reversible, the reaction will approach equilibrium state at infinite time (Figure S10):

$$2M \rightleftharpoons B + I \tag{3}$$
$$k'$$

Therefore, an equilibrium constant  $(K_{eq})$  can be defined as:

$$K_{eq} = \frac{[B] \times [I]}{[M]^2} = \frac{a_B a_I}{a_m^2}$$
(4)

With an assumption that  $a_j = \gamma_j x_j$  with  $x_j$  as the molar fraction and  $\gamma_j = 1$ . In practice we can define  $x/2 = x_B = x_I$  and  $x_M = 1 - x$  so that:

$$K_{eq} = \frac{x^2}{4(1-x)^2}$$
(5)


We assume that the molar fraction is proportional to the change in absorption e.g.  $x = \frac{\Delta Abs_m}{Abs_{0,m}}$  where  $Abs_{0,m}$  and  $\Delta Abs_m$  are the initial absorbance of the mixed phase and the change in absorbance, respectively.  $\Delta Abs_m$  was obtained from the pre-exponential factor in the kinetic curve fitting while  $Abs_{0,m}$  was obtained from the peak area of the exciton peak in the mixed phase. The obtained K<sub>eq</sub> are presented in Figure 3e and

Table S2. At T = 25 °C, with the increase in intensity, the equilibrium is strongly shifted towards mixed parent structure. However, with further increase in temperature, at T = 56 °C and 71 °C, the impact of increased intensity on the equilibrium gradually is reduced. Finally, at T = 84 °C, equilibrium under all three illuminating conditions is almost the same. It is important to notice that under the illumination of 6.5 mW cm<sup>-2</sup>, the equilibrium in the whole temperature range strongly depends on the temperature (as it is valid for the rate of segregation). With the increase in temperature, the equilibrium shifts towards the mixed phase. This is meaningful as because the reaction entropy change, expected to be quite relevant in this process, will dominate at large T. However, for 9.5 mW cm<sup>-2</sup> and 12.0 mW cm<sup>-2</sup> the equilibrium is weakly temperature-dependent in the range from 25 °C to 71 °C, similar to the observed two distinct regions in Arrhenius plots.

Additionally, we can consider enthalpy changes calculated from the Van't Hoff diagram for the segregation process at different intensities. A plot of  $\ln(K_{eq})$  vs 1/T is shown in Figure 3f-h and the linear curve is described by the Van't Hoff equation as

$$\ln(\mathbf{K}_{eq}) = -\frac{\Delta H}{RT} + \frac{\Delta S}{R} \tag{6}$$

where  $\Delta H$  and  $\Delta S$  are the enthalpy change and the entropy change of PHS. Data at higher temperature for 9.5 mW cm<sup>-2</sup> and 12 mW cm<sup>-2</sup> (TDR region) have been fitted separately, as the reaction under these illumination intensities can no longer be described as a single linear function. The enthalpy change under 6.5 mW cm<sup>-2</sup> is  $-152 \pm 9$  kJ mol<sup>-1</sup>. The large negative value indicates that photoinduced segregation is a highly exothermic reaction, meaning that increase in temperature shifts the equilibrium towards the mixed parent phase. For illumination intensities of 9.5 mW cm<sup>-2</sup> and 12 mW cm<sup>-2</sup> in TDR region, we observe enthalpy changes of  $-344 \pm 66$  kJ mol<sup>-1</sup> and  $-197 \pm 87$  kJ mol<sup>-1</sup>, in agreement with the behavior observed for lower illumination intensity. In LDR, however, we observe a significant reduction of the enthalpy change to  $2 \pm 8$  kJ mol<sup>-1</sup> and  $7 \pm 11$  kJ mol<sup>-1</sup>. The obtained uncertainties in this region are comparable to the uncertainty obtained for 6.5 mW/cm<sup>2</sup>, but due to the low values of  $\Delta H$  resulting from weak dependence on temperature (dependence close to horizontal line) relative uncertainties of parameters are large. Low enthalpy change suggests that the shift from the temperature-dependent regime to the intensity regime results in the significant decrease in the magnitude of heat release. In the intensity regime, the increase of the intensity results in a significant decrease of equilibrium constant with only a slight change in the amount of released heat. To elucidate the effects of light intensity, the enthalpy change and entropy change with different intensities are plotted in Figure S11a. The intensity driven equilibrium shift can be described by the entropy change which was obtained from the y-intercept of the Van't Hoff diagram. The reaction entropy changed from  $-478 \pm 28$  J K<sup>-1</sup> mol<sup>-1</sup> for 6.5 mW cm<sup>-2</sup> to  $-1020 \pm 190$  J K<sup>-1</sup> mol<sup>-1</sup> and  $-597 \pm 249$  J K<sup>-1</sup> <sup>1</sup> mol<sup>-1</sup> for 9.5 mW cm<sup>-2</sup> and 12 mW cm<sup>-2</sup>, respectively, in TDR. The negative value reveals that the entropy in the mixed phase is larger than that in the segregated phases. Also, the equilibrium is shifted to the mixed state because the increased intensity magnifies the amount of entropy loss. In LDR, however, the reaction entropy reduced to  $5 \pm 25$  J K<sup>-1</sup> mol<sup>-1</sup> and  $-2 \pm 33$  J K<sup>-1</sup> mol<sup>-1</sup> for 9.5 mW cm<sup>-2</sup> and 12 mW cm<sup>-2</sup>, respectively. In this case as well, the uncertainties are similar to that obtained for 6.5 mW/cm<sup>2</sup> (likely limited by experimental uncertainties of our setup), but the low value of  $\Delta S$  results in large relative uncertainty. The significant changes in entropy loss and large uncertainties of fitted parameters illustrate that with the increase of illumination power the process can no longer be well described by a simple Van't Hoff model, i.e.  $\Delta H$  and  $\Delta S$  are temperature dependent in this range. This illustrates that with increase of the illumination power additional mechanisms become significant.



**Figure 3.** (a)  $\ln(k)$  versus temperature plot and b) Arrhenius plots for the photoinduced halide segregation processes in PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> film at T = 25, 41, 56, 71 and 84 °C under (b) 6.5 mW cm<sup>-2</sup>, (c) 9.5 mW cm<sup>-2</sup> and (d) 12.0 mW cm<sup>-2</sup>. (e)  $\ln(K_{eq})$  versus temperature plot and Van 't Hoff plots of PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> film at T = 25, 41, 56, 71 and 84 °C under (f) 6.5 mW cm<sup>-2</sup>, (g) 9.5 mW cm<sup>-2</sup> and (h) 12.0 mW cm<sup>-2</sup>. The polynomial fit curves (dot line) show that data are converging at high temperature. Solid lines are linear fit of the data. Red and yellow shadings indicate temperature-dominated region (TDR) and light-dominated region (LDR), respectively.


In parallel to  $K_{eq}$ , we can extract the Gibbs free energy that directly expresses if the reaction is shifted towards the reactant or the product. A full heatmap diagram of this quantity is shown in Figure S11b. The calculated reaction Gibbs free energy shifts from negative to positive with increased temperature at 6.5 mW cm<sup>-2</sup>. It coincides with the thermodynamic based model where halide mixing/demixing process is temperature dependent.<sup>18-20</sup> On the other hand, increase in illumination power is found to increase the Gibbs free energy and thus favor the mixing process. This observation hints the remixing behavior of MHP at strong illumination condition.<sup>39-41</sup> We speculate that the observed shifts in *k* and  $K_{eq}$  are caused by light induced surface deformation<sup>42</sup> such as redistribution of strain gradient<sup>40</sup> or microstructure evolution.<sup>41</sup> Photothermal effect, which has been shown to remix segregated phases,<sup>41</sup> is excluded since the light intensity here is significantly lower than the reported power and the power dependent effect is fading at high temperature. However, it could play a role at higher illumination intensities, especially since measured temperature increase of the sample using a thermocouple for the short duration of the experiment (30 min) may not necessarily reflect localized heating of the perovskite layer due to low thermal conductivities of glass and MHP.

The observed PHS process can be described with Gibbs free energy surface in the Figure S11c. An equilibrium condition is established between the parent mixed phase and halide segregated phases. Under illumination, the populated photoexcited state features a free energy surface which is favorable to the halide segregation. However, the shape of the ground free energy surface connecting the mixed and segregated phases ( $\Delta_r G^0$ ) depends on the temperature (Figure S11d). Entropy and enthalpy control the reaction equilibrium (and its behavior with temperature) while equilibration pathways take place regardless of illumination intensity. With increasing intensity, the PHS occurs faster because of the larger photoexcited population (effectively corresponding to a barrier reduction), but at the same time the free energy difference is reduced, likely due to microstructure evolution, slightly affecting the properties of reactant and product state. At large intensity the reaction is then shifted towards the mixed parent phase.

It should be noted that the observed trends (in terms of segregation and segregation suppression at a certain illumination intensity and/or temperature) are highly reproducible. However, the kinetics can vary from sample to sample, as illustrated in Figure S12. This is not surprising, since the ion diffusion is dependent on native defects and grain boundaries, which would be affected by glove box atmosphere at the time of synthesis, variations in manual application of antisolvent, etc. An important factor affecting the starting absorption spectrum and XRD pattern was found to be the use of different precursor combinations to obtain the films with the same final stoichiometry, as illustrated in Figure S13. It can be observed that there is a significant difference in the films prepared from 2PPABr+PbI<sub>2</sub> and 2PPAI+PbBr<sub>2</sub>, indicating that

the precursors used affect the mixing in the final film, with shift possibly occurring either due to internal strain or due to differences in mixing at nanoscale. Finally, it should be noted that at high illumination powers and/or temperatures the encapsulation of the samples plays an important role, since delamination can occur.<sup>43</sup> As shown in Figure S14, using a cover glass held together with clips (method previously reported<sup>18</sup>) results in erroneous result of suppression of segregation (likely due to increased ion diffusion due to partial solvation due to moisture ingress), while segregation followed by re-mixing with significant intensity drop is obtained with epoxy-only encapsulation, and finally no remixing is observed when edges of the epoxy+cover glass encapsulated sample are additionally sealed by tape. At room temperature, epoxy+cover glass encapsulation is sufficient and reliable, but simple cover glass held together with clips is not, as illustrated in Figure S15. This strongly indicates that the experimental investigations must be performed on properly encapsulated samples to ensure reproducibility.

Finally, while  $PPA_2Pb(Br_{0.5}I_{0.5})_4$  is exhibiting interesting and unique dependence of PHS behavior at moderate light intensities, PHS under higher intensity (1 Sun or 100 mW/cm<sup>2</sup>) is highly relevant for practical applications. Thus, we examined the behavior of the  $PPA_2Pb(Br_{0.5}I_{0.5})_4$  under higher illumination power, as shown in Figure 4, as well as Figures S16-S18.



**Figure 4.** *In-situ* absorption spectra of PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> films at (a-c) 25 °C and (d-f) 84 °C for 30 mins of illumination with white light intensities of (a,d) 50 mW cm<sup>-2</sup> (b,e) 75 mW/cm<sup>2</sup> and (c,f) 100 mW/cm<sup>2</sup>.

While photosegregation observed is strong at higher illumination intensities, different trends are observed for different illumination powers. At room temperature the PHS is marked at 0.5 Sun and even more at 0.75 and 1 Sun. However, in all cases illumination at 84°C results in some suppression of the segregation. At 1 Sun illumination, the segregation rate decreases with increasing temperature (Table S3), different from the observed temperature dependence at low illumination intensity of 6.5 mW/cm<sup>2</sup>. This led to a false estimation of activation energy with a negative value (Figure S19) and implies that the segregation consists of multistep processes under strong illumination. At the microscopic level, the increased light intensity will result in increased photogenerated hole concentration, with the hole trapping at iodide sites potentially increasing lattice instability,<sup>22</sup> and thus enhancing the segregation. For 0.5 Sun illumination at 84°C we can observe some suppression of the segregation. We have already mentioned strain redistribution<sup>40</sup> and microstructure evolution<sup>41</sup> as possible reasons for segregation suppression. Another possible connected phenomenon is the photostriction effect. It is known that MHPs exhibit photostriction effect under illumination, and the lattice compression saturates with increasing light intensity.<sup>44</sup> Since lattice compression increases the activation barrier for phase segregation,<sup>45</sup> this could contribute to the PHS suppression at light intensities, with further increase in the intensity and consequent increase in hole concentration, followed by increased hole trapping and polaron-related deformation, resulting in segregation dominance at high light intensity. The observed dependence of the PHS on temperature and light intensity indicates that additional mechanisms, different from the recognized processes (polaroninduced strain leading to the formation of I-rich domains, valence band edge variation, localization of holes at iodide sites, concentration gradients of halide species, defect involvement),<sup>32</sup> exists in these samples.

These elements point to a different regime for the PHS compared to low illumination powers: as both internal and polaron-induced lattice strain can serve as driving forces for PHS,<sup>21</sup> we speculate that in some materials lattice compression can result in suppression of PHS for certain certain light intensities. The coexistence of strain effects with other more general critical elements, such as hole and defects densities, may also play a role in approaching saturation regimes. Obtained results further suggest that the critical temperature for photo-miscibility gap (the temperature where segregation will stop) depends not only the temperature but also the interaction of material properties, exposed environment and illumination condition.<sup>32</sup>

Observation of such unusual dependence of PHS on light intensity and temperature in PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)4 films highlights the need for comprehensive *in situ* characterizations which would enable obtaining the information on structure/strain under illumination and at elevated temperature, such as *in situ* XRD or Raman spectroscopy under white light illumination. At the same time, it is highly relevant to perform the measurements either for encapsulated samples or under inert atmosphere since the presence of moisture and oxygen can not only cause degradation but also significantly alter the observed kinetics, likely due to higher ion mobility in the presence of moisture.

We studied the PHS process in PPA<sub>2</sub>Pb(Br<sub>0.5</sub>I<sub>0.5</sub>)<sub>4</sub> film with the *in-situ* absorption measurement. The segregation process under Xe light was successfully captured without any interruption of remixing in dark. Our observations indicate that the increase in temperature can result in the suppression of PHS despite the increase in the segregation rate with the increase in temperature. Also, we spotted the distinctive impacts of temperature and excitation intensity on PHS. At low intensity, the PHS process is primarily controlled by the temperature and the photoinduced segregation is hindered at high temperature because of its highly exothermic nature. Increasing the intensity to moderate level (~0.1 Sun) results in the emergence of dominance of other mechanisms and consequently more complex behavior is observed with two distinct regions present in temperature dependence. Thus, under excitations of 9.5 mW/cm<sup>2</sup> and 12 mW/cm<sup>2</sup>, shifting of the equilibrium to the mixed state is observed. Further increase in intensity, however, results in segregation rate decreases with temperature different from observed behavior at low illumination intensity of 6.5 mW/cm<sup>2</sup>. This complex dependence on the intensity and temperature highlights the need for the development of *in situ* characterization techniques, as well as the necessity for further investigations utilizing different spacer cations to develop improved understanding of PHS in layered halide perovskites.

## AUTHOR INFORMATION

## Corresponding Authors

Jasminka Popović: jpopovic@irb.hr, Aleksandra B. Djurišić: dalek@hku.hk

#### Author Contributions

<sup>‡</sup>These authors contributed equally. T. L. L. prepared the samples, performed the measurements, analyzed the results and prepared initial draft of the manuscript. Z.R and A. A. S. performed the measurements at 0.5-1 Sun illumination intensities. J. P. and A. B. D. designed the study, analyzed and interpreted results and wrote the manuscript. L. G. analyzed and interpreted results. The final manuscript was written through contributions of all authors. All authors have given approval to the final version of the manuscript.

Notes

The authors declare no competing financial interest.

## ACKNOWLEDGMENT

This work was supported by the Seed Funding for Basic Research and the Seed Funding for Strategic Interdisciplinary Research Scheme of the University of Hong Kong, RGC CRF projects 7018-20G, NSFC project 6207032617 and PZS-2019-02-2068 project financed by the "Research Cooperability" Program of the Croatian Science Foundation and European Union from the European Social Fund under the Operational Programme Efficient Human Resources 2014-2020.

## SUPPORTING INFORMATION

Absorption spectra of mixed halide perovskites with different spacer cations, absorption spectra and XRD patterns of PPA<sub>2</sub>PbBr<sub>4</sub>, PPA<sub>2</sub>PbBr<sub>2</sub>I<sub>2</sub>, and PPA<sub>2</sub>PbI<sub>4</sub>, spectrum of Xe lamp and comparison of *in situ* absorption spectrum with absorption spectrum measured using an absorption spectrometer for PPA<sub>2</sub>PbBr<sub>2</sub>I<sub>2</sub>, *in situ* absorption spectra and corresponding segregation traces for different powers and temperatures, enthalpy and entropy changes, Gibbs free energy reconstructed 2D heatmap and illustration of behavior of free energy reaction surface, effects of precursors used on film properties, effects of encapsulation method on photoinduced segregation behavior at 25°C and 84°C, rate and equilibrium constants for different conditions. This material is available free of charge via the Internet at http://pubs.acs.org.

# References

1. Tao, S.; Schmidt, I.; Brocks, G.; Jiang, J.; Tranca, I.; Meerholz, K.; Olthof, S., Absolute energy level positions in tin- and lead-based halide perovskites. *Nat. Commun.* **2019**, *10*, 2560.

2. Karlsson, M.; Yi, Z.; Reichert, S.; Luo, X.; Lin, W.; Zhang, Z.; Bao, C.; Zhang, R.; Bai, S.; Zheng, G.; Teng, P.; Duan, L.; Lu, Y.; Zheng, K.; Pullerits, T.; Deibel, C.; Xu, W.; Friend, R.; Gao, F., Mixed halide perovskites for spectrally stable and high-efficiency blue light-emitting diodes. *Nat. Commun.* **2021**, *12*, 361.

3. Yuan, S.; Cui, L.-S.; Dai, L.; Liu, Y.; Liu, Q.-W.; Sun, Y.-Q.; Auras, F.; Anaya, M.; Zheng, X.; Ruggeri, E.; Yu, Y.-J.; Qu, Y.-K.; Abdi-Jalebi, M.; Bakr, O. M.; Wang, Z.-K.; Stranks, S. D.; Greenham, N. C.; Liao, L.-S.; Friend, R. H., Efficient and Spectrally Stable Blue Perovskite Light-Emitting Diodes Employing a Cationic  $\pi$ -Conjugated Polymer. *Adv. Mater.* **2021**, *33* (11), 2103640.

4. Al-Ashouri, A.; Köhnen, E.; Li, B.; Magomedov, A.; Hempel, H.; Caprioglio, P.; Márquez José, A.; Morales Vilches Anna, B.; Kasparavicius, E.; Smith Joel, A.; Phung, N.; Menzel, D.; Grischek, M.; Kegelmann, L.; Skroblin, D.; Gollwitzer, C.; Malinauskas, T.; Jošt, M.; Matič, G.; Rech, B.; Schlatmann, R.; Topič, M.; Korte, L.; Abate, A.; Stannowski, B.; Neher, D.; Stolterfoht, M.; Unold, T.; Getautis, V.; Albrecht, S., Monolithic perovskite/silicon tandem solar cell with >29% efficiency by enhanced hole extraction. *Science* **2020**, *370* (6522), 1300-1309.

5. Kamaraki, C.; Klug, M. T.; Green, T.; Perez, L. M.; Case, C., Perovskite/silicon tandem photovoltaics: Technological disruption without business disruption. *Appl. Phys. Lett.* **2021**, *119* (7), 070501.

6. Wang, R.; Huang, T.; Xue, J.; Tong, J.; Zhu, K.; Yang, Y., Prospects for metal halide perovskite-based tandem solar cells. *Nat. Photonics* **2021**, *15* (6), 411-425.

7. Best Research-Cell Efficiency Chart. U.S. National Renewable Energy Laboratory: U.S. National Renewable Energy Laboratory, Vol. 2021.

8. Richter, A.; Hermle, M.; Glunz, S. W., Reassessment of the Limiting Efficiency for Crystalline Silicon Solar Cells. *IEEE J. Photovolt.* **2013**, *3* (4), 1184-1191.

9. Hoke, E. T.; Slotcavage, D. J.; Dohner, E. R.; Bowring, A. R.; Karunadasa, H. I.; McGehee, M. D., Reversible photo-induced trap formation in mixed-halide hybrid perovskites for photovoltaics. *Chem. Sci.* **2015**, *6* (1), 613-617.

10.Hu, L.; Guan, X.; Chen, W.; Yao, Y.; Wan, T.; Lin, C.-H.; Pham, N. D.; Yuan, L.; Geng, X.; Wang, F.; Huang, C.-Y.; Yuan, J.; Cheong, S.; Tilley, R. D.; Wen, X.; Chu, D.; Huang, S.; Wu, T., Linking Phase Segregation and Photovoltaic Performance of Mixed-Halide Perovskite Films through Grain Size Engineering. *ACS Energy Lett.* **2021**, *6* (4), 1649-1658.

11. Yang, T. C.-J.; Fiala, P.; Jeangros, Q.; Ballif, C., High-Bandgap Perovskite Materials for Multijunction Solar Cells. *Joule* **2018**, *2* (8), 1421-1436.

12. Yoon, S. J.; Kuno, M.; Kamat, P. V., Shift Happens. How Halide Ion Defects Influence Photoinduced Segregation in Mixed Halide Perovskites. *ACS Energy Lett.* **2017**, *2* (7), 1507-1514.

13.Balakrishna, R. G.; Kobosko, S. M.; Kamat, P. V., Mixed Halide Perovskite Solar Cells. Consequence of Iodide Treatment on Phase Segregation Recovery. *ACS Energy Lett.* **2018**, *3* (9), 2267-2272.

14. Brivio, F.; Caetano, C.; Walsh, A., Thermodynamic Origin of Photoinstability in the CH<sub>3</sub>NH<sub>3</sub>Pb(I<sub>1-x</sub>Br<sub>x</sub>)<sub>(3)</sub> Hybrid Halide Perovskite Alloy. *J. Phys. Chem. Lett.* **2016**, *7* (6), 1083-1087.

15. Bischak, C. G.; Hetherington, C. L.; Wu, H.; Aloni, S.; Ogletree, D. F.; Limmer, D. T.; Ginsberg, N. S., Origin of Reversible Photoinduced Phase Separation in Hybrid Perovskites. *Nano Lett.* **2017**, *17* (2), 1028-1033.

16. Draguta, S.; Sharia, O.; Yoon, S. J.; Brennan, M. C.; Morozov, Y. V.; Manser, J. M.; Kamat, P. V.; Schneider, W. F.; Kuno, M., Rationalizing the light-induced phase separation of mixed halide organic-inorganic perovskites. *Nat. Commun.* **2017**, *8*, 200.

17. Ruth, A.; Brennan, M. C.; Draguta, S.; Morozov, Y. V.; Zhukoyskyi, M.; Janko, B.; Zapol, P.; Kuno, M., Vacancy-Mediated Anion Photosegregation Kinetics in Mixed Halide Hybrid Perovskites: Coupled Kinetic Monte Carlo and Optical Measurements. *ACS Energy Lett.* **2018**, *3* (10), 2321-2328.

18. Elmelund, T.; Seger, B.; Kuno, M.; Kamat, P. V., How Interplay between Photo and Thermal Activation Dictates Halide Ion Segregation in Mixed Halide Perovskites. *ACS Energy Lett.* **2020**, *5* (1), 56-63.

19. Wang, X.; Ling, Y. C.; Lian, X. J.; Xin, Y.; Dhungana, K. B.; Perez-Orive, F.; Knox, J.; Chen, Z. Z.; Zhou, Y.; Beery, D.; Hanson, K.; Shi, J.; Lin, S. C.; Gao, H. W., Suppressed phase separation of mixed-halide perovskites confined in endotaxial matrices. *Nat. Commun.* **2019**, *10*, 695.

20. Pavlovetc, I. M.; Ruth, A.; Gushchina, I.; Ngo, L.; Zhang, S. B.; Zhang, Z. M.; Kuno, M., Distinguishing Models for Mixed Halide Lead Perovskite Photosegregation via Terminal Halide Stoichiometry. *ACS Energy Lett.* **2021**, *6* (6), 2064-2071.

21. Choe, H.; Jeon, D.; Lee, S. J.; Cho, J. Mixed or Segregated: Toward Efficient and Stable Mixed Halide Perovskite-Based Devices. *ACS Omega* **2021**, 6, 24304–24315.

22. DuBose, J. T.; Kamat, P. V. Hole Trapping in Halide Perovskites Induces Phase Segregation. *Acc. Mater. Res.* **2022**, 3, 761–771.

23. Xiao, Z.; Zhao, L.; Tran, N. L.; Lin, Y. L.; Silver, S. H.; Kerner, R. A.; Yao, N.; Kahn, A.; Scholes, G. D.; Rand, B. P., Mixed-Halide Perovskites with Stabilized Bandgaps. *Nano Lett.* **2017**, *17* (11), 6863-6869.

24. Zhou, Y.; Wang, F.; Cao, Y.; Wang, J.-P.; Fang, H.-H.; Loi, M. A.; Zhao, N.; Wong, C.-P., Benzylamine-Treated Wide-Bandgap Perovskite with High Thermal-Photostability and Photovoltaic Performance. *Adv. Energy Mater.* **2017**, *7* (22), 1701048.

25. Mathew, P. S.; DuBose, J. T.; Cho, J. S.; Kamat, P. V., Spacer Cations Dictate Photoinduced Phase Segregation in 2D Mixed Halide Perovskites. *ACS Energy Lett.* **2021**, *6* (7), 2499-2501.

26. Cho, J.; Mathew, P. S.; DuBose, J. T.; Kamat, P. V., Photoinduced Halide Segregation in Ruddlesden–Popper 2D Mixed Halide Perovskite Films. *Adv. Mater.* **2021**, *33* (48), 2105585.

27. Wang, Y.-R.; Senocrate, A.; Mladenović, M.; Dučinskas, A.; Kim, G. Y.; Rothlisberger, U.; Milić, J. V.; Moia, D.; Grätzel, M.; Maier, J., Photo De-Mixing in Dion-Jacobson 2D Mixed Halide Perovskites. *Adv. Energy Mater.* **2022**, 2200768.

28. Cho, J.; Jeffrey T. DuBose, J. T.; Le, A. N. T.; Kamat, P. V. Suppressed Halide Ion Migration in 2D Lead Halide Perovskites. *ACS Materials Lett.* **2020**, 2, 565–570.

29. Liu, Y.; Wang, M.; Ievlev, A. V.; Ahmadi, A.; Keum, J. K.; Ahmadi, M.; Hu, B.; Ovchinnikova, O. S. Photoinduced iodide repulsion and halides-demixing in layered perovskites. *Mater. Today* Nano **2022**, 18, 100197.

30. Shi, E.; Yuan, B.; Shiring, S. B.; Gao, Y.; Akriti, Guo, Y.; Su, C.; Lai, M.; Yang, P.; Kong, J.; Savoie, B. M.; Yu, Y.; Dou, L. Two-dimensional halide perovskite lateral epitaxial heterostructures. *Nature* **2020**, 580, 614-620.

31. Brennan, M. C.; Draguta, S.; Kamat, P. V.; Kuno, M., Light-Induced Anion Phase Segregation in Mixed Halide Perovskites. *ACS Energy Lett.* **2018**, *3* (1), 204-213.

32. Wang, Y. R.; Kim, G. Y., Kotomin, E.; Moia, D.; Maier, J. Photo de-mixing in mixed halide perovskites: the roles of ions and electrons. *J. Phys. Energy* **2022**, *4*, 011001.

33. Polyzoidis, C.; Rogdakis, K.; Kymakis, E. Indoor Perovskite Photovoltaics for the Internet of Things—Challenges and Opportunities toward Market Uptake. *Adv. Energy Mater.* **2021**, *11*, 2101854.

34. Muhammad, B. T.; Kar, S. Stephen, M.; Leong, W. L. Halide perovskite-based indoor photovoltaics: recent development and challenges. *Materials Today Energy* **2022**, *23*, 100907.

35. Du, K.-Z.; Tu, Q.; Zhang, X. Han, Q.; Liu, J.; Zauscher, S.; Mitzi, D. B., Two-Dimensional Lead(II) Halide-Based Hybrid Perovskites Templated by Acene Alkylamines: Crystal Structures, Optical Properties, and Piezoelectricity. *Inorg. Chem.* **2017**, *56* (15), 9291-9302.

36. Gong, X.; Voznyy, O.; Jain, A.; Liu, W.; Sabatini, R.; Piontkowski, Z.; Walters, G.; Bappi, G.; Nokhrin, S.; Bushuyev, O.; Yuan, M.; Comin, R.; McCammant, D.; Kelley, S. O.; Sargent, E. H., Electron–phonon interaction in efficient perovskite blue emitters. *Nat. Mater.* **2018**, *17*, 550-556.

37. Knight, A. J.; Wright, A. D.; Patel, J. B.; McMeekin, D. P.; Snaith, H. J.; Johnston, M. B.; Herz, L. M., Electronic Traps and Phase Segregation in Lead Mixed-Halide Perovskite. *ACS Energy Lett.* **2019**, *4* (1), 75-84.

38. Bischak, C. G.; Wong, A. B.; Lin, E.; Limmer, D. T.; Yang, P.; Ginsberg, N. S., Tunable Polaron Distortions Control the Extent of Halide Demixing in Lead Halide Perovskites. *J. Phys. Chem. Lett.* **2018**, *9* (14), 3998-4005.

39. Guo, Y. X.; Yin, X. T.; Liu, D.; Liu, J.; Zhang, C.; Xie, H. X.; Yang, Y. W.; Que, W. X., Photoinduced Self-healing of Halide Segregation in Mixed-halide Perovskites. *ACS Energy Lett.* **2021**, *6* (7), 2502-2511.

40. Mao, W. X.; Hall, C. R.; Bernardi, S.; Cheng, Y. B.; Widmer-Cooper, A.; Smith, T. A.; Bach, U., Light-induced reversal of ion segregation in mixed-halide perovskites. *Nat. Mater.* **2021**, *20*, 55-61.

41. Vicente, J. R.; Kordesch, M. E.; Chen, J., Stabilization of mixed-halide lead perovskites under light by photothermal effects. *J. Energy Chem.* **2021**, *63*, 8-11.

42. Leng, K.; Abdelwahab, I.; Verzhbitskiy, I.; Telychko, M.; Chu, L.; Fu, W.; Chi, X.; Guo, N.; Chen, Z.; Chen, Z.; Zhang, C.; Xu, Q.-H.; Lu, J.; Chhowalla, M.; Eda, G.; Loh, K. P., Molecularly thin two-dimensional hybrid perovskites with tunable optoelectronic properties due to reversible surface relaxation. *Nat. Mater.* **2018**, *17*, 908-914.

43. Wang, Y.; Ahmad, I.; Leung, T.; Lin, J.; Chen, W.; Liu, F.; Ng, A. M. C.; Zhang, Y.; Djurišić, A. B.; Encapsulation and Stability Testing of Perovskite Solar Cells for Real Life Applications. *ACS Mater. Au* **2022**, 2 (3), 215–236.

44. Wei, T. C.; Wang, H. P.; Li, T. Y.; Lin, C. H.; Hsieh, Y. H.; Chu, Y. H.; He, J. H. Photostriction of CH<sub>3</sub>NH<sub>3</sub>PbBr<sub>3</sub> Perovskite Crystals. *Adv. Mater.* **2017**, 29, 1701789.

45. Muscarella, L. A.; Hutter, E. M.; Wittmann, F.; Woo, Y. W.; Jung, Y. K.; McGovern, L.; Versluis, J.; Walsh, A.; Bakker, H. J.; Ehrler, B. Lattice Compression Increases the Activation Barrier for Phase Segregation in Mixed-Halide Perovskites. *ACS Energy Lett.* **2020**, 5, 3152–3158.



